


ME-2200

RF Isolation Fabric

ME-2200 OC

RF Isolation Fabric with Outer Cover



ME-2200 is a simple solution for effective RF signal attenuation in many commercial applications. It provides -100 dB RF isolation from 100 MHz to 1 GHz and more than -85 dB to 18GHz. Very light, thin, flexible, wear and tear resistant, it can be applied directly to studs, standard sheetrock and other structures using simple and inexpensive methods. The product is well suited to both new and retrofit construction. It provides a good degree of isolation typically seen with metal sheathing. It offers

significant savings in labor, shipping and construction costs and needs virtually no physical space unlike competitive materials.

ME-2200 does not require specialized tools or techniques to apply. This flexible product comes in rolls. Special shapes can be fabricated for custom applications. It can be modified to your specific requirements.

Typical applications:

- Security uses, including RF shielding to prevent the use of cellular telephones and other communication devices (including covert ones) in selected areas.
- Construction of RF quiet zones for scientific and developmental research.
- Isolation of noisy RF sources to protect sensors and receivers.
- Isolation of cell tower transmitters to protect building inhabitants.
- Extraneous Artifact Reduction in MRI and other High RF Flux Applications.
- Medical uses, including RF shielding for hospital instrumentation, and Intensive Care Units.
- Wideband EMI Shielding.

FEATURES:

Construction:

ME-2200 is a single layer flexible panel consisting of isolation ground plane material.

ME-2200 OC is the above material with an acrylic nylon pack cloth outer cover and is manufactured to the customer's size and shape requirements. It is available in standard black or grey. It can be waterproofed for outdoor applications. Grommets or D rings can be added at customer request.

Size:

ME-2200 Typically supplied in rolls of 52 in minimum (132 cm). It can be cut to customer size requirements.

ME-2200 OC is made to order as per customer requirements and should not be cut.

Color:

ME-2200 is copper colored on both sides.

Mechanical properties:

Substrate	Rip stop Nylon
Metal	Nickel over Silver
Basis Weight	12-14 oz. /yard ²
Thickness	0.05 in (0.0127 cm)
Weight	Typically less than 0.1 lbs./ft ² (0.45 kg/m ²)
Thermal Stability	Range of -40°F to 160°F
Elongation MD	9% (per ASTM D5035)
Tensile Strength	7.5 /18.5 lb. /in (CMD / MD)
Hazardous Material	None
Visual Defects:	Uniform surface texture and appearance
Thermal Cycles:	10 cycles, 1 hr/-20°F - 1 hr/70° F, no adverse effects
Low Temperature Impact:	-20°F, 1.5 ft. lbs., and no adverse effects
Effects of Liquids Oil:	No adverse effects after 1000 hours (ASTM-B-117)
Effects of Liquids, Water:	Less than 6% increase in volume (ASTM-D-471)

Performance:

-100 dB RF isolation from 100 MHz to 1 GHz

Greater than -85 dB RF isolation from 1 GHz to over 18 GHz

Nail, screw and staple punctures have no effect on signal attenuation